

PRODUCT DATA

Item number 01729

DS/LT

Replaces none – 1st edition



Mounting Corners (PP) October 1999

Upper Foil:

- ◆ 100% acid free, archival safe polypropylene (PP).
- ◆ Thickness: 80 µm (3,15 Mil).
- ◆ Colour: Transparent.

Lower Foil:

- ◆ 100% acid free, archival safe polypropylene (PP).
- ◆ Thickness: 80 µm (3,15 Mil).
- ◆ Colour: Transparent.
- ◆ Adhesive:
 - ◆ Long life adhesive, especially selected for archival application.
 - ◆ Pressure sensitive acrylic adhesive.
 - ◆ No stain and no adhesive penetration.
 - ◆ High tack.
 - ◆ pH-level: Neutral.
 - ◆ Adhesive never touches mounted object.
- ◆ Liner:
 - ◆ Siliconized, totally chlorine-free (TCF), wood-free kraft paper.
 - ◆ Weight: 130 g/m².
 - ◆ Colour: White.

Temperature:

- ◆ Application temperature: Above +10°C (50°F).
- ◆ Service temperature: -10°C... +60°C (14°F ... 140°F).
- ◆ Long-term heat exposure may result in discoloration of the product.

PAT Test:

- ◆ The lower foil has been submitted for testing and has passed the test.

General Remark:

- ◆ Customers are recommended to make their own assessment of our products under their own conditions, for their own requirements.

It is 3L-Consumer products policy continuously to review our products, and where appropriate implement modifications. We therefore reserve the right to change the specifications of our products and test methods without prior notice. The information on this data sheet is to the best of our knowledge and based on information from our suppliers, in compliance with the truth.